

# TECHNICAL DATA SHEET

Version: 3.0 - Last Update: 04/05/2021

## TAPE PRO 1060

### PREMIUM HIGH TEMPERATURE INDUSTRIAL GRADE MASKING TAPE

#### TYPICAL APPLICATIONS:

TAPE PRO 1060 offers superior performance for demanding painting and coating applications. It sticks to a wide variety of surfaces, stays positioned and gives outstanding clean paint lines. Its superior temperature resistance makes it a great choice for demanding coating works.

#### FEATURES & BENEFITS

- Easy Unwind
- High Temperature Resistance
- Easy & Clean removal

#### PROPERTIES

Color:	Ivory
Backing:	Semi-crepe paper
Adhesive:	Natural Rubber
Country of Origin:	Italy

#### TECHNICAL DATA

Property	Nominal Value	Unit
Total Thickness	139	µm
Paper Weight	65	g/m <sup>2</sup>
Adhesion to Steel	250	g/cm
Tensile Strength	4	kg/cm
Elongation at Break	7	%
Rolling Ball Tack	1	cm
Temperature Resistance	100° C	60min
Removal Time	5	days indoor

This Technical Data Sheet (TDS) is provided by BOCK for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. BOCK expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. BOCK does not exclude liability for death or personal injury arising from its negligence or fraud. BOCK refers to Bock Middle East FZCO and its subsidiaries.

